

## **Respiratory protection: filters**

## **Description and composition:**

**This filter is manufactured with high-resistance materials** that do not produce noxious effects to the user's health and hygiene.


It is designed to offer excellent protection against: inorganic gases and vapours and organic gases and vapours with a boiling point higher than 65 °C.

This filter may be used with all Medop half masks with bayonet connection.

## Maximum level of use:

Gas and vapour filter - Use level 1: limit value 1000 ppm; 0.1% volum.

Weight: 94 g





Bayonet connection



Protection against: gases and vapours



Category III

## **Respiratory protection: filters**

Standard and certification	EN 14387 CE
Applications	Solvents, manure handling. Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers.  The expiry date is marked in the following way:  XX/XXXX (MONTH/YEAR)
Directions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume.  Immediately leave the work area and replace your filters if during use:  - You find it hard to breathe.  - You feel dizzy or vertigo.  - You smell or taste contaminant.
Presentation  - * **** * **************************	8 units per box. 18 boxes per carton. Measurements: 483 x 262 x 507 mm
Bar code	GTIN-13: 8423173871901 GTIN-14: 38423173871902

