



Filters ABE2 P2 R



Respiratory protection: filters

Description and composition

This filter is manufactured with high-resistance materials that do not produce noxious effects to the user's health and hygiene.

It is designed to offer excellent protection against: Inorganic gases and vapours and organic gases and vapours with the boiling point higher than 65°C. Also sulphur dioxide and hydrogen chloride

This filter may be used with all Medop half masks with bayonet connection.

Maximum level of use:

Gas and vapour filter - Use level 2: limit value 5000 ppm; 0.5% volum.

Weight: 94 gr.



Bayonet connection




Protection against: gases, vapours and particles



PAD filter

Ref.	Product
912566	Filtro ABE2P2

Respiratory protection: filters

Standard and certification	EN 14387, EN 143 CE
Applications	Treatment with solvents, varnishes, wood preservatives, epoxy resins and polyesters, conventional paints (that do not contain isocyanates). Most common sectors: Manufacturing and maintenance, aeronautical production, automotive sector, shipyards, ink and varnish production, color pigments, adhesives, paints, resins and works with gases and inorganic vapours. Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage-Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf-life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way: ⌚ xx/xxxx (Month/Year)
Directions use	This filter filters contaminated air, but it does not provide oxygen. This, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: -You find it hard to breathe -You feel dizzy or vertigo -You smell or taste contaminant
Presentation	6 units per box 18 boxes per carton Measurements: 483x262x507mm. 
Bar code	GTIN-13: 8423173886691 GTIN-14: 38423173886692

