



A2B2E2K2 Hg P3 R D Filter



Respiratory protection: filters

Description and composition:

This filter is manufactured with high-resistance materials that do not produce noxious effects to the user's health and hygiene.


It is designed to offer excellent protection against: organic vapours with a boiling point below 65 °C, inorganic gasses and vapours, acid gasses, sulphurous anhydride (SO₂), ammonia (NH₃) and their organic derivatives, mercury vapours, dust, smoke and mist.

Reusable filter: can be used for more than one workday.
Passes dolomite tests: less obstruction for longer.

This filter can be used with full masks with unified threaded connector EN 148-1.

Respiratory resistance:
At 30 l/min: 1.4 mbar
At 95 l/min: 5.8 mbar

Weight: 380 g



Universal threaded connection





Protection against: organic vapours with a boiling point below 65 °C, inorganic gasses and vapours, acid gasses, sulphurous anhydride, ammonia and derivatives, mercury vapours, dust, smoke and mist.



Category III

Ref.	Product
912451	A2B2E2K2 Hg P3 R D Filter

Respiratory protection: filters

Standard and certification	Directive 89/686/CEE EN 14387:2004 +EN143:2000+A1:2006
Applications	Asbestos removal, work with chrome-containing paint, work with beech and oak wood, stainless steel, cutting with laser light, certain types of welding, dust sweeping, electrical stations... Typical industrial applications for these filters include mining, construction, products made from metal, pharmaceuticals... Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way: XX/XXXX (MONTH/YEAR)  Store between -20 °C and +50 °C, with a relative humidity under 80%.
Instructions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: - You find it hard to breathe - You feel dizzy or vertigo - You smell or taste contaminant
Presentation	4 units per box 14 unit carton (56 units) Box measurements: 22 x 22 x 11 cm Carton measurements: 60 x 40 x 43 cm 
Bar code	GTIN-13: 8423173885458 GTIN-14: 38423173885459

