



AXP3 NR D Filter



Respiratory protection: filters

Description and composition:

This filter is manufactured with high-resistance materials that do not produce noxious effects to the user's health and hygiene.

It is designed to offer excellent protection against: Organic vapours with a boiling point below 65 °C. Good warning properties

NON-reusable filter: limited periods of usage. Depending on the type of substance, can not be used for more than one working day (can only be used once).

Passes dolomite tests: less obstruction for longer.


This filter can be used with full masks with unified threaded connector EN 148-1.

Respiratory resistance:

At 30 l/min: 1.2 mbar

At 95 l/min: 4.6 mbar

Weight: 367 g



Universal threaded connection



Protection against:
Organic vapours with a boiling point below 65 °C, dust, smoke and mists.




Category III

CAT. III

Ref.	Product
912450	AXP3 NR D Filter

Respiratory protection: filters

Standard and certification	Directive 89/686/CEE EN 14387:2004 +EN143:2000+A1:2006
Applications	Jobs that imply the use of unstable gasses: acetaldehyde, acetones, dichloromethane, ethers, solvents, etc. Some typical industrial applications for these filters are laboratories and particle application... Do not use in atmospheres with less than 19,5% oxygen content volume
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way: XX/XXXX (MONTH/YEAR) 🔑 Store between -20 °C and +50 °C, with a relative humidity under 80%.
Instructions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: - You find it hard to breathe - You feel dizzy or vertigo - You smell or taste contaminant Not recommended when different organic substances with different boiling points are being mixed, since when absorbing one substance, another, more volatile substance could be desorbed.
Presentation	4 units per box 14 unit carton (56 units) Box measurements: 22 x 22 x 11 cm Carton measurements: 60 x 40 x 43 cm
	
Bar code	GTIN-13: 8423173885441 GTIN-14: 3 8423173885442

