



B2 filter



Respiratory protection: filters

Description and composition:

This filter is manufactured with high-resistance materials that do not produce noxious effects to the user's health and hygiene.

It is designed to offer excellent protection against: inorganic gases and vapours.

This filter may be used with all Medop half masks with a threaded connection.

Maximum level of use:

Gas and vapour filter - Use level 1: limit value 1000 ppm; 0.1% volum.

Weight: 96 g



Threaded connection





Protection against:
gases and vapours



Category III

Ref.	Product
906.440	B2 filter

Respiratory protection: filters

Standard and certification	EN 14387 CE
Applications	Work with inorganic gases and vapours. Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way:  XX/XXXX (MONTH/YEAR)
Directions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: <ul style="list-style-type: none">- You find it hard to breathe.- You feel dizzy or vertigo.- You smell or taste contaminant.
Presentation	8 units per box. 18 boxes per carton. Measurements: 483 x 262 x 507 mm
	
Bar code	GTIN-13: 8423173130060 GTIN-14: 38423173130061

