



0% METAL	WEIGHT 28 ^g	EN166 EN170 EN172	UV 400	FT KN
-------------	---------------------------	-------------------------	-----------	----------

COMFORT, SECURITY AND DESIGN IN ONE SINGLE PAIR OF SPECTACLES

Highly impact-resistant
Polycarbonate + TPC Frame

Flexible temples for greater user comfort

Flexible nasal bridge

Temples adjustable in angle and length with 3 positions to adapt to all users

Excellent panoramic vision **without distortion**


Clear version

CERTIFIED Anti-scratch (K) and Anti-fogging (N) treatments on all versions

NEUTRAL EYE PROTECTION DESCRIPTION AND COMPOSITION:



SOLAR VERSION (EN172):



Temples with adjustable angle and length: in 3 positions

Frame and lenses made of Polycarbonate for high impact-resistance. **Upper protection** made of rubber to create a barrier from suspended particles, adding extra protection by cushioning and absorbing force in case of impact.

Sporty wraparound design without lateral distortion to provide excellent upper and side protection.

VERSATILITY: Flexible temples with adjustable length (3 positions) and angle (3 positions)

COMFORT: **Multi-injected frame for excellent adaptation to the user** with flexible, non-slip temple-ends that increase user comfort, and for greater adherence between the different parts of the frame, preventing parts of the spectacles from coming loose. Also, **non-slip temples** that avoid slipping during use. Flexible nasal bridge that absorbs impact.

CERTIFIED ANTI-FOGGING TREATMENT (N) for perfectly **clear** vision even in sudden temperature changes.

CERTIFIED ANTI-SCRATCH TREATMENT (K) for **longer lasting** lenses.

0% SILICONE

Available in	Frame marking	Lens marking	Ref.
Clear Polycarbonate with CERTIFIED Anti-scratch and Anti-fogging treat.	M EN 166 FT	2C-1.2 M 1 FTKN	913790
Solar Polycarbonate with CERTIFIED Anti-scratch and Anti-fogging treat.		5-2.5 M 1 FTKN	913791


NEUTRAL EYE PROTECTION

INFORMATION MARKINGS		
Standard and Certification	EN 166 (Personal eye protection Specifications) EN 170 (Ultraviolet filters) EN 172 (Solar protection filters for work use)	
Optical class	1	Continuous work
Mechanical resistance	F	Resistance to low energy impacts (steel ball from 6 mm at 45 m/s)
	T	Resistance to high speed impacts at extreme temperatures
	K	Resistance to surface damage by fine particles
	N	Fogging resistance
Types of filter	2C-1.2	Ultraviolet filters with good colour recognition (74.4% minimum visible transmittance)
	5-2.5	Filters for medium coloured solar protection, not suitable for driving. (Light transmission between 18% - 43%)

MATERIALS	
Frame	POLYCARBONATE + TPE
Nasal bridge	TPE
Temple-ends	TPE
Lenses	POLYCARBONATE (6.5)

WEIGHT AND OTHER COMPONENTS	
Silicone *	Not present
Metal	Not present
Weight	28 g

* Although this PPE does not contain silicone it is recommended to perform tests and try the product in painting areas before use.

OTHER FEATURES	
Applications	Jobs with risk of impact • Jobs requiring multiple PPEs simultaneously • Outdoor jobs that require sun protection • Jobs that require UV protection Example sectors: Driving, Food, Quality Control, Construction, Forest and agricultural work, Piece inspectors, Paper/Graphic art, Laboratories, Maintenance, Machinery, Industrial assembly, Plastic, Factory technicians, Textiles, Workshops, Loading and unloading work, Metal work, etc.
Conservation Storage Expiry	Glasses have no expiration date but it is recommended they be replaced after suffering an impact even when there are no visible signs of damage from the impact. For better conservation of the glasses, they must be stored in a cool and ventilated place, away from moisture, dirt and dust. It is recommended that you use a suitable case for storage and transport.
Instructions Use How to use	Glasses should be regularly cleaned with clean, warm water and soap, no abrasives or solvents. Rinse in water and dry with a clean, soft and absorbent cloth. For a more thorough cleaning (disinfection), please use a dry cloth dipped in alcohol. Never use any other type of solvent. Also recommended for lens care is Medop's Anti-Fog Cleaning Spray. It is necessary to regularly inspect the state of the spectacles , and replace them if they have deteriorated in any way. Please ensure that the risk present in the workplace corresponds to the field of use of these spectacles.
Presentation	12 units per box. 300 units per carton. Polybag dimensions: 266.6 x 106 mm 
Bar code	913790 GIN-13: 8423173890513 GIN-14: 18423173890510 913791 GIN-13: 8423173890520 GIN-14: 18423173890527