



Hood



Body protection: aluminised clothing

Description and composition:

Hood with gold visor filtering infra-red radiation.

Made in 100% para-aramid Aratex (450 g/m²). Fabric especially designed to protect from convective heat, radiating heat and metal splashes. Available with:

- 4 mm width laminated mirrored visor. Measurements: 100 x 200 mm
- 1 mm width flexible polycarbonate mirrored visor. Measurements: 100 x 200 mm

With adjustable straps. Also available with a 5 cm Velcro fastener on both versions of the visor.

This PPE is recommended for industrial activities where the user has:

- Brief contact with small flames (A1)
- Convective heat sources up to 80 Kw/m² (B1)
- Radiating heat sources up to 20 Kw/m² (C4)
- Molten aluminium and iron splashes (D3)
- Small splashes of molten metal (E3)
- Contact heat (up to 250 °C) (F3)



Infra-red visor



100% para-aramid Aratex fabric (450 g/m²)



Also available with a Velcro fastener

Size: One size. **EN ISO 13688:2013 / EN ISO 11612**
Category III PPE

Ref:	Product	
901.286	Hood with polycarbonate visor	A1B1C4D3E3F3 4-5 UHL FT
901.287	Hood with polycarbonate visor	A1B1C4D3E3F3 4-4 UHL 1 BT 9
911.126	Hood with 5 cm Velcro fastener and glass visor	A1B1C4D3E3F3 4-5 UHL FT
911.127	Hood with 5 cm Velcro fastener and polycarbonate visor	A1B1C4D3E3F3 4-4 UHL 1 BT 9
900.477	Glass visor	4-5 UHL FT
900.478	Polycarbonate visor	4-4 UHL 1 BT 9

MARKING

	Limited flame propagation	A1 A2
	Convective heat	B1 B2 B3
	Radiant heat	C1 C2 C3 C4
	Molten iron splashes	D1 D2 D3
	Molten aluminium splashes	E1 E2 E3
	Contact heat	F1 F2 F3

Body protection: aluminised clothing

Standard and Certification	EN ISO 13688:2013 / EN ISO 11612 / EN 166 / EN 177 Category III PPE
Applications	PPE for industrial use in the following sectors: foundries, metal industry, pyrotechnics, furnace repair, cement works, steelworks, etc.
Conservation Storage - Expiry	Protect from light and dust. Not washable. Clean with a damp sponge. Do not dry clean.
Directions Use	This hood is designed to be fitted and adjusted easily and without tools. It must always be used with a protection helmet with a visor, which must have a minimum width of 2 cm and a maximum width of 7 cm (approximately). Correct performance of the garment requires it to be correctly adjusted. This equipment is designed for use during short periods.
Presentation	Individually packed: 1 unit.
Bar code	Hood with polycarbonate visor GTIN-13: 8423173100292 GTIN-14: 18423173100299 Hood with polycarbonate visor GTIN-13: 8423173870898 GTIN-14: 18423173870895 Hood with 5 cm Velcro fastener and glass visor GTIN-13: 8423173870881 GTIN-14: 18423173870888 Hood with 5 cm Velcro fastener and polycarbonate visor GTIN-13: 8423173100308 GTIN-14: 18423173100305 Glass visor GTIN-13: 8423173092238 GTIN-14: 18423173092235 Polycarbonate visor GTIN-13: 8423173092245 GTIN-14: 18423173092242

