



DIVA PRO

0%
METAL

WEIGHT
22 g

EN166

FTKN

DESIGNER SAFETY SPECTACLES:
MODERN AND IN TRENDY COLOURS

Highly impact-resistant **Xylex** frame

Very flexible temples with co-injected tips for greater comfort and earplug fastening hole

Transparent frames that allow vision without obstacles

Extra-soft thermoplastic nasal bridge to increase the sensation of comfort

Clear/blue version

Excellent upper and side protection

CERTIFIED Anti-scratch and Anti-fogging coatings on all versions

NEUTRAL EYE PROTECTION

DESCRIPTION AND COMPOSITION:



Clear/Black version



Clear/Green version



Clear/blue version

Frames and lenses made with **Xylex**, for high impact resistance and good resistance to chemical products. FT marking: Resistance to low-energy and high-velocity impacts at extreme temperatures. **Nasal bridge and anti-slip temples** that avoid slipping during use and improve comfort.

DESIGN with transparent frame for vision without obstacles. Upper and side protection. Nasal bridge and temple tips made of extra-soft thermoplastic, which increases comfort and prevents the occurrence of allergic reactions.

VERSATILITY: Very flexible temples that adapt to all physiognomies.

COMFORT: Temples with co-injected ends for greater adaptation and comfort for the user and **compatibility with other PPEs.** Co-injected with extra-soft TPR at the nasal bridge, providing comfort and security and helping to absorb and disperse the force of the impacts.

CERTIFIED ANTI-FOGGING COATING (N marking) for perfectly **clear** vision even in sudden temperature changes. **CERTIFIED ANTI-SCRATCH COATING** (K marking) for **longer lasting** lenses.

Neutral vision	Colour	Frame marking	Lens marking	Ref. Size S	Ref. Size M
Polycarbonate with Anti-scratch and Anti-fogging coatings	Clear/Green	MEDOP EN 166 FT CE	2C-1.2 M 1 FTKN CE	913894	913895
	Clear/Black			913896	913897
	Clear/Blue			913898	913899
PC prescription lenses	Clear/Green Clear/Black Clear/Blue		2C-1.2 M 1 FTK CE		
CR-39 Prescription			M 1 SK CE		


NEUTRAL EYE PROTECTION

MARKING INFORMATION		
Standard and Certification	EN 166 (Individual eye protection. Specifications)	
Optical class	1	Continuous work
Additional requirements	K	Resistance to surface damage by fine particles
	N	Fogging resistance
Mechanical resistance	F	Resistance to low energy impacts (steel ball from 6 mm at 45 m/s)
	T	Resistance to high speed impacts at extreme temperatures

MATERIALS	
Frame	XYLEX
Nasal bridge	THERMOPLASTIC
Temple-ends	THERMOPLASTIC
Lenses	POLYCARBONATE (Base 4.5)

WEIGHT AND OTHER COMPONENTS	
Silicone*	Not present
Metal	Not present
Weight	22 grams.

* Although this PPE does not contain silicone, it is recommended to perform tests and try the product in painting areas before use.

OTHER FEATURES	
Uses	Jobs with risk of impacts. Work environments with high temperatures. Environments with electricity. Jobs that combine plant and office work. Example sectors: Construction, F&B, textile, paper and graphic arts, agricultural activities, forestry, automotive industry, plastic, etc.
Conservation Storage Expiry	Glasses have no expiration date but it is recommended they be replaced after suffering an impact even when there are no visible signs of damage from the impact. For better conservation of the glasses, they must be stored in a cool and ventilated place, away from moisture, dirt and dust. It is recommended that you use a suitable case for storage and transport.
Instructions Use How to use	Glasses should be regularly cleaned with clean, warm water and soap, no abrasives or solvents. Rinse in water and dry with a clean, soft and absorbent cloth. For a more thorough cleaning (disinfection), please use a dry cloth dipped in alcohol. Never use any other type of solvent. Also recommended for lens care is Medop's Anti-Fog Cleaning Spray. It is necessary to regularly inspect the state of the spectacles , and replace them if they have deteriorated in any way. Please ensure that the risk present in the workplace corresponds to the field of use of these spectacles.
Presentation	10 units per box. 300 units per carton. Polybag dimensions: 305 x 117 mm 
Bar code	DIVA PRO 913894 GIN-13: 8423173891695 GIN-14: 18423173891692 913895 GIN-13: 8423173891701 GIN-14: 18423173891708 913896 GIN-13: 8423173891718 GIN-14: 18423173891715 913897 GIN-13: 8423173891725 GIN-14: 18423173891722 913898 GIN-13: 8423173891732 GIN-14: 18423173891739 913899 GIN-13: 8423173891749 GIN-14: 18423173891746