



GP Xtreme



Neutral eye protection

Description and composition:

Rubber front (Dupont 42 degrees).
1.7 mm polycarbonate visor.

Non-slip, adjustable, elastic strap.
Foam frame lining for greater comfort.

Latex free.

Dielectric: with no metal parts.

All polycarbonate lenses have an anti-abrasion treatment.

Weight: 81 g



Non-slip fastening



CE anti-fogging



Rubber front

Ref.	Product	MARKING	
		Frame	Lenses
907085	Clear polycarbonate spectacles. Anti-fogging treatment	166 M 3 4 9 FT	M 1 B 3 4 9 N

Neutral eye protection

Standard and certification	EN 166 / EN 172
Applications	Impact protection. Sectors: agricultural activities, forestry, hunting, lathe work, polishers or mills, automotive industry, construction, quarries, outdoor work, hot environments or places with different temperatures, etc.
Conservation Storage - Expiry	In order to maintain the spectacles in good condition, keep them in a clean, dry place in their appropriate case.
Directions Use	Cleaning: use warm water and a neutral soap. Do not use abrasives or solvents. Rinse in water and dry with a soft cloth. Medop anti-fogging cleaning spray is also recommended. We advise regular inspection of the protectors, and their replacement if they have deteriorated in any way. Please ensure that the risk present in the workplace corresponds with the field of use of these protectors.
Presentation	12 units per box. 25 boxes per carton.
Bar code	907085 GIN-13: 8423173135539 GIN-14: 68423173135531

