



Highprotection



Hearing protection: headphones

Description and composition:

Buffers made in hypo-allergenic materials. Thermoplastic materials: ABS, PVC.

This model incorporates cushioned headband and earpads, as well as height adjustable ear cups for greater comfort and adaptability.

Folding headphones, making them easy to store after use.

Ear cups are luminous orange, making these headphones very high visibility. Ideal for activities where visual detection of the worker is important.

Net weight: 217 g


SNR 32



Adjustable height



Cushioned ear pads




0%
metal

0% metal

Ref.	Product
911.259	Highprotection

Characteristics table	
Cushioned headband	✓
Adjustable height	✓
Cushioned ear pads	✓
Electronic	✗
0% metal	✓

Hearing protection: headphones

Standard and certification	EN 352-1 CE																																		
Applications	The product offers high attenuation, whereby it is especially recommended for high-noise environments and activities where worker visibility is important. Work environments with a noise level between 102 dB and 117 dB. Sectors: F&B, chemical, metallurgy, carpentry, automotive industry, construction, graphic arts, airports, etc.																																		
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																		
Directions Use	Clean regularly with soap and water. Inspect regularly and replace immediately when damaged or very worn. This equipment is for personal use and should not be used by several people. The headphones must be worn continually in noisy areas.																																		
Presentation	1 unit per box. 20 units per carton.																																		
																																			
Bar code	GTIN-13: 8423173872311 GTIN-14: 78423173872310																																		
Technical data:	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1,000</th> <th>2,000</th> <th>4,000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Assumed attenuation</td> <td>16.9</td> <td>19.9</td> <td>28.1</td> <td>36.6</td> <td>31.2</td> <td>37.5</td> <td>35.0</td> </tr> <tr> <td>Typical deviation</td> <td>2.2</td> <td>2.5</td> <td>2.0</td> <td>2.3</td> <td>2.2</td> <td>2.1</td> <td>2.6</td> </tr> <tr> <td>Average attenuation</td> <td>19.1</td> <td>22.4</td> <td>30.1</td> <td>38.9</td> <td>33.4</td> <td>39.6</td> <td>37.6</td> </tr> </tbody> </table> <table border="1"> <tr> <td>SNR</td> <td>32</td> </tr> </table>	Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000	Assumed attenuation	16.9	19.9	28.1	36.6	31.2	37.5	35.0	Typical deviation	2.2	2.5	2.0	2.3	2.2	2.1	2.6	Average attenuation	19.1	22.4	30.1	38.9	33.4	39.6	37.6	SNR	32
Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000																												
Assumed attenuation	16.9	19.9	28.1	36.6	31.2	37.5	35.0																												
Typical deviation	2.2	2.5	2.0	2.3	2.2	2.1	2.6																												
Average attenuation	19.1	22.4	30.1	38.9	33.4	39.6	37.6																												
SNR	32																																		

