

The (average) diameter of under 7mm makes it easier to insert

Conical shape for easy insertion

Quick-expansion earplug for easy insertion

Soft polyurethane foam hypoallergenic material

Colour patterns with a unique design

DESCRIPTION AND COMPOSITION:

Made out of polyurethane foam, with a non-porous, soft texture, making them more resistant to dirt.

Their cone-shape and their compact size makes insertion and adaptation easier.

They expand quickly and easily in the ear canal for simpler and faster adjustment.

Ideal for high- and medium-noise level environments.

Designed with colour patterns for a unique style

Single-use hypoallergenic earplugs.

SNR: 37 dB

Available in	Colour	SNR	Ref.
200 pairs of HISS earplugs per box	Blue	37	914308
Bag with 500 pairs of HISS earplugs (appropriate for using with Medop's earplug dispenser)	Blue	37	914412

HEARING PROTECTION EARPLUGS

TECHNICAL INFORMATION																																	
Standard and Certification	EN 352-2:2020																																
SNR	37																																
Material	Polyurethane foam																																
Attenuation table	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>8000</th> </tr> </thead> <tbody> <tr> <td>Mean attenuation</td> <td>28.7</td> <td>32.2</td> <td>39.6</td> <td>40.5</td> <td>37.9</td> <td>42.2</td> <td>46.3</td> </tr> <tr> <td>Standard deviation</td> <td>3.6</td> <td>5.2</td> <td>5.4</td> <td>4.3</td> <td>2.9</td> <td>3.1</td> <td>5.4</td> </tr> <tr> <td>Assumed protection</td> <td>25.1</td> <td>27.0</td> <td>34.2</td> <td>36.2</td> <td>35.0</td> <td>39.1</td> <td>40.9</td> </tr> </tbody> </table>	Frequency in Hz	125	250	500	1000	2000	4000	8000	Mean attenuation	28.7	32.2	39.6	40.5	37.9	42.2	46.3	Standard deviation	3.6	5.2	5.4	4.3	2.9	3.1	5.4	Assumed protection	25.1	27.0	34.2	36.2	35.0	39.1	40.9
	Frequency in Hz	125	250	500	1000	2000	4000	8000																									
	Mean attenuation	28.7	32.2	39.6	40.5	37.9	42.2	46.3																									
	Standard deviation	3.6	5.2	5.4	4.3	2.9	3.1	5.4																									
	Assumed protection	25.1	27.0	34.2	36.2	35.0	39.1	40.9																									
<p>SNR: 37 dB SNR_M: 39.5 dB SNR_S: 2.5 dB</p> <p>H: 37 dB H_M: 39.4 dB H_S: 2.5 dB</p> <p>M: 35 dB M_M: 38.1 dB M_S: 2.9 dB</p> <p>L: 30 dB L_M: 34.0 dB L_S: 3.6 dB</p>	<table border="1"> <tbody> <tr> <td>Global attenuation in frequencies</td> <td>37</td> </tr> <tr> <td>Mean attenuation in frequencies</td> <td>39.5</td> </tr> <tr> <td>Assumed attenuation in frequencies</td> <td>2.5</td> </tr> </tbody> </table>	Global attenuation in frequencies	37	Mean attenuation in frequencies	39.5	Assumed attenuation in frequencies	2.5																										
Global attenuation in frequencies	37																																
Mean attenuation in frequencies	39.5																																
Assumed attenuation in frequencies	2.5																																

OTHER FEATURES	
Uses	<p>Workplaces with high temperatures.</p> <p>Work environments with a high noise level.</p> <p>General industrial use.</p>
Conservation Storage	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.
Instructions Use How to use	<p>This equipment is for personal use and should not be used by several people.</p> <p>The earplugs must be worn continually in noisy areas.</p>
Presentation	<p>Box with 200 pairs (in individual bags). 10 box carton.</p> <p>Bag with 500 pairs. 10 bags per carton</p>
Bar code	<p>914308: GIN-13 8423173894306 GIN-14: 18423173894303</p> <p>914412: GIN-13 8423173894856 GIN-14: 18423173894853</p>