



KIBO

GREATER PROTECTION, MAXIMUM COMFORT

0%
METAL

WEIGHT
134^g

EN166
EN170
EN172

UV
400

3459
BTKN

Ventilated version for greater comfort in environments with sudden temperature changes. Avoids condensation on the lenses.

Flexible and very light frame for long periods of use

Overflow channel for liquids.

2.5 cm elastic band that dissipates pressure, reducing tight feeling

Quick-release mechanism for one-hand operation

Ventilated clear version

CERTIFIED Anti-scratch and Anti-fogging treatments on all versions

COMPATIBLE WITH PRESCRIPTION GLASSES



NOT VENTILATED CLEAR VERSION (EN170):

This version offers protection from fine dust and gas particles (5), and the lenses offer ultra-violet protection (EN 170).



VENTILATED SOLAR VERSION (EN172):

Excellent solar protection for exterior work (UV 400).

NEUTRAL EYE PROTECTION DESCRIPTION AND COMPOSITION:

Frame made of PVC and lenses made of polycarbonate for high impact-resistance. **Total eye protection for the user.**

VERSATILITY: Available in **solar version** for use in outdoor work. **Wide field of vision.** Available in ventilated and not ventilated version.

COMFORT: **Quick-release** clasp. Adjustable elastic strap that dissipates pressure for greater comfort.

CERTIFIED ANTI-FOGGING TREATMENT (N) for perfectly **clear vision** even in sudden temperature changes.

CERTIFIED ANTI-SCRATCH TREATMENT (K) for **longer lasting** lenses.

UV 400. Excellent solar protection for exterior work.

Available in	Frame marking	Lens marking	Ref.
Ventilated Clear Polycarbonate with CERTIFIED Anti-scratch and Anti-fogging treat.	3 4 9 M EN 166 BT CE	2C-1.2 M 1 BT 9 KN	913783
Clear polycarbonate, not ventilated, with CERTIFIED anti-scratch and anti-fogging treatment.	3 4 5 9 M EN 166 BT CE	2C-1.2 M 1 BT 9 KN	913784
Ventilated Solar Polycarbonate with CERTIFIED Anti-scratch and Anti-fogging treat.	3 4 9 M EN 166 BT CE	5C-2.5 M 1 BT 9 KN	913785


NEUTRAL EYE PROTECTION

INFORMATION MARKINGS			
Standard and Certification	EN 166 (Personal eye protection Specifications) EN 170 (Ultraviolet filters) EN 172 (Solar protection filters for work use)		
Optical class	1	Continuous work	
Mechanical resistance	B	Resistance to medium-energy impacts	3 Liquids
	T	Resistance to high speed impacts at extreme temperatures	4 Thick dust particles
	K	Resistance to surface damage by fine particles	5 Fine dust and gas particles
	N	Fogging resistance	9 Molten metal and hot solids
Types of filter	2C-1.2	Ultraviolet filters with good colour recognition (74.4% minimum visible transmittance)	
	5-3.1	Filters for solar protection + ultraviolet filter. For use in Bright Sunlight (Visible transmittance between 8% and 17.8%) and UV spectrum (Visible transmission between 3.2% and 8.5%)	

MATERIALS	
Frame	PVC (lateral clip made of nylon)
Nasal bridge	PVC
Elastic strap	ELASTIC POLYESTER
Lenses	POLYCARBONATE (BASE 5.5)

WEIGHT AND OTHER COMPONENTS	
Latex *	Not present
Metal	Not present
Weight	134 g

* Although this PPE does not contain latex it is recommended to perform tests and try the product.

OTHER FEATURES	
Applications	Jobs with risk of impact · Jobs requiring multiple PPEs simultaneously · Outdoor jobs that require sun protection · Jobs that require UV protection · Jobs with sudden changes of temperature. Example sectors: Vehicles, Construction, Textile, Food, Agricultural activities, Stationery/Graphic arts, Painters, Mechanics, Maintenance, Laboratories, Quality Control, Workshops, Plastics, Industrial assembly, Forestry and agricultural operations, Plant technicians, Steelworks, Piece inspectors, etc.
Conservation Storage Expiry	Glasses have no expiration date but it is recommended they be replaced after suffering an impact even when there are no visible signs of damage from the impact. For better conservation of the glasses, they must be stored in a cool and ventilated place, away from moisture, dirt and dust. It is recommended that you use a suitable case for storage and transport.
Instructions Use How to use	Glasses should be regularly cleaned with clean, warm water and soap, no abrasives or solvents. Rinse in water and dry with a clean, soft and absorbent cloth. For a more thorough cleaning (disinfection), please use a dry cloth dipped in alcohol. Never use any other type of solvent. Also recommended for lens care is Medop's Anti-Fog Cleaning Spray. It is necessary to regularly inspect the state of the spectacles , and replace them if they have deteriorated in any way. Please ensure that the risk present in the workplace corresponds to the field of use of these spectacles.
Presentation	6 units per box. 60 units per carton. Polybag dimensions: 266.6 x 106 mm 
Bar code	913783 GIN-13:8423173890445 GIN-14: 18423173890442
	913784 GIN-13: 8423173890452 GIN-14: 18423173890459
	913785 GIN-13: 8423173890469 GIN-14: 18423173890466