

Neutral eye protection

Description and composition:

Nylon sports frames for excellent protection and comfort.

3 millimetre thick foam interior allows a perfect fit to the face of the user and improves comfort. It is an accessory which can be removed.

A very versatile model with certified clear, solar, polarized and photochromic lenses.

Maximum **comfort** thanks to flat temples, perfect compatibility with other PPEs.

Highly impact-resistant polycarbonate lenses with **UV 400 filter:** 100% protection against harmful ultra-violet light.

F marking: Resistance to low-energy impact.

Colour: Weight: 35 g Base: 10

		MARKING	
Ref.	Product	Lenses	Frame
912903	Clear polycarbonate anti-scratch and anti-fogging spectacles	2C-1,2 M 1 F CE	M EN166 F CE
912886	Polycarbonate anti-scratch and anti-fogging sunglasses	5-2.5 M 1 F CE	M EN166 F CE
912887	Polarized polycarbonate anti-scratch spectacles	5-3,1 M 1 F CE	M EN166 F CE

www.medop.es

Flat and thin temples

Foam interior that provides

Wide range of CE lenses

comfort and fit

Neutral eye protection

Standard and certification	UNE-EN 166:2002 - UNE-EN 170:2003 - UNE-EN 172/A1:2000		
Applications	Protection against low-energy impacts. Industries: mining, quarries, aeronautics, renewable energy, refineries, automotive industry, sports, transport, maintenance, electronics. And in general any outdoor or indoor work with risk of impact.		
Conservation Storage - Expiry	In order to maintain the spectacles in good condition, keep them in a clean, dry place in their appropriate case.		
Instructions Use	Polycarbonate cleaning: use warm water and a neutral soap. Do not use abrasives or solvents. Rinse in water and dry with a soft cloth. Medop anti-fogging cleaning spray is also recommended. We advise regular inspection of the protectors, and their replacement if they have deteriorated in any way.		
Presentation	Individual polybag with bar code 12 units per box 10 boxes per carton		
Bar code	912903GTIN-13: 8.423.173.888.909GTIN-14: 18.423.173.888.678912886GTIN-13: 8.423.173.888.664GTIN-14: 18.423.173.888.661912887GTIN-13: 8.423.173.888.671GTIN-14: 18.423.173.888.906		

