



Murmullo



Hearing protection: earplugs

Description:

Made out of polyurethane foam, with a non-porous, soft texture, making them more resistant to dirt.

Hypo-allergenic. Their cone-shape makes insertion and adaptation easier.

They gently expand inside the ear canal. Ideal for highly or moderately noisy environments.

SNR: 39dB


Weight: 1.1 g

EN 352-2 CE

Ref.	Product
910.280	Box (500 units)
906.980	Dispenser box (200 pairs)

Characteristics table


Washable	X
Hypo-allergenic	✓
Reusable	X
Single use	✓
Detectable	X
Cord	X
Nominal size	6-13




Soft polyurethane foam



Conical shape for easy insertion.



Hearing protection: earplugs

Standard and certification	EN 352-2 CE																																							
Applications	Workplaces with high temperatures. Exposure to continuous noise. Work environments with a high noise level: 108 dB to 122 dB. General industrial use.																																							
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																							
Directions Use	This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas.																																							
Presentation																																								
	910.280	Pairs in individual bags. Bag: 500 pairs. 10 bags per carton.																																						
	906.980	Pairs in individual bags. Dispenser box with 200 pairs in individual bags. 10 boxes per carton.																																						
Bar code	910.280	GTIN-13: 8423173834999 GTIN-14: 88423173834995																																						
	906.980	GTIN-13: 8423173134587 GTIN-14: 88423173134583																																						
Attenuation table	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1,000</th> <th>2,000</th> <th>4,000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Assumed attenuation</td> <td>38,1</td> <td>37,3</td> <td>42,7</td> <td>41,2</td> <td>39,1</td> <td>45,3</td> <td>48,1</td> </tr> <tr> <td>Typical deviation</td> <td>5,6</td> <td>4,7</td> <td>4,9</td> <td>5,4</td> <td>2,7</td> <td>4,5</td> <td>4,4</td> </tr> <tr> <td>Average attenuation</td> <td>32,5</td> <td>32,5</td> <td>37,7</td> <td>35,8</td> <td>36,4</td> <td>40,9</td> <td>43,7</td> </tr> </tbody> </table> <table border="1"> <tbody> <tr> <td>Global attenuation in frequencies</td> <td>High (H) H = 38</td> <td>Mid (M) M = 37</td> <td>Low (L) L = 35</td> <td>SNR</td> <td>39</td> </tr> </tbody> </table>		Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000	Assumed attenuation	38,1	37,3	42,7	41,2	39,1	45,3	48,1	Typical deviation	5,6	4,7	4,9	5,4	2,7	4,5	4,4	Average attenuation	32,5	32,5	37,7	35,8	36,4	40,9	43,7	Global attenuation in frequencies	High (H) H = 38	Mid (M) M = 37	Low (L) L = 35	SNR	39
Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000																																	
Assumed attenuation	38,1	37,3	42,7	41,2	39,1	45,3	48,1																																	
Typical deviation	5,6	4,7	4,9	5,4	2,7	4,5	4,4																																	
Average attenuation	32,5	32,5	37,7	35,8	36,4	40,9	43,7																																	
Global attenuation in frequencies	High (H) H = 38	Mid (M) M = 37	Low (L) L = 35	SNR	39																																			

