



New Song



Hearing protection: earplugs

Description:

Expansible foam earplug.

Softly and safely expands without producing irritation.

Hypo-allergenic.

Easy insertion and adaptation.

SNR: 27 dB

Weight: 1.07 g


EN 352-2 CE



Easy insertion




Expansible foam



Ref.	Product
911.670	New Song

Characteristics table	
Washable	✗
Hypo-allergenic	✓
Reusable	✗
Single use	✓
Detectable	✗
Cord	✗
Nominal size	8-13

Hearing protection: earplugs

Standard and certification	EN 352-2 CE																																																		
Applications	Workplaces with high temperatures. Exposure to continuous noise. Work environments with a high noise level: 100 dB to 115 dB. General industrial use.																																																		
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																																		
Directions Use	This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas.																																																		
Presentation	<div></div> <p>Pairs in individual bags. Dispenser box with 200 pairs in individual bags. 10 boxes per carton.</p>																																																		
Bar code	GTIN-13: 8423173095741 GTIN-14: 88842317309579																																																		
Attenuation table	<table><tr><td>Frequency in Hz</td><td>63</td><td>125</td><td>250</td><td>500</td><td>1,000</td><td>2,000</td><td>4,000</td><td>8,000</td></tr><tr><td>Average attenuation</td><td>21.6</td><td>22.1</td><td>25.4</td><td>26.3</td><td>25.8</td><td>31.4</td><td>41.6</td><td>43.6</td></tr><tr><td>Typical deviation</td><td>5.7</td><td>5.1</td><td>4.0</td><td>4.6</td><td>4.0</td><td>4.9</td><td>3.6</td><td>5.1</td></tr><tr><td>Assumed attenuation</td><td>15.6</td><td>17.0</td><td>21.4</td><td>21.7</td><td>21.8</td><td>26.5</td><td>38.0</td><td>38.5</td></tr></table> <table><tr><td>Global attenuation in frequencies</td><td>High (H) H = 28</td><td>Mid (M) M = 23</td><td>Low (L) L = 22</td><td>SNR</td><td>27</td></tr></table>									Frequency in Hz	63	125	250	500	1,000	2,000	4,000	8,000	Average attenuation	21.6	22.1	25.4	26.3	25.8	31.4	41.6	43.6	Typical deviation	5.7	5.1	4.0	4.6	4.0	4.9	3.6	5.1	Assumed attenuation	15.6	17.0	21.4	21.7	21.8	26.5	38.0	38.5	Global attenuation in frequencies	High (H) H = 28	Mid (M) M = 23	Low (L) L = 22	SNR	27
Frequency in Hz	63	125	250	500	1,000	2,000	4,000	8,000																																											
Average attenuation	21.6	22.1	25.4	26.3	25.8	31.4	41.6	43.6																																											
Typical deviation	5.7	5.1	4.0	4.6	4.0	4.9	3.6	5.1																																											
Assumed attenuation	15.6	17.0	21.4	21.7	21.8	26.5	38.0	38.5																																											
Global attenuation in frequencies	High (H) H = 28	Mid (M) M = 23	Low (L) L = 22	SNR	27																																														

