



# Overall



## Body protection: aluminised clothing

### Description and composition:


**Made in 100% para-aramid Aratex (450 g/m<sup>2</sup>).** Fabric especially designed to protect from convective heat, radiating heat and metal splashes. "Double mirror" system: double aluminised layer + basic material, meaning maximum protection. Open-backed 3/4 overall. Adjustable waist straps.

This PPE is recommended for industrial activities where the user has:

- Brief contact with a small flame (A1)
- Convective heat sources up to 80 Kw/m<sup>2</sup> (B1)
- Radiating heat sources up to 20 Kw/m<sup>2</sup> (C4)
- Molten aluminium and iron splashes (D3)
- Small splashes of molten metal (E3)
- Contact heat (up to 250 °C) (F2)



Adjustable waist straps



100% para-aramid (450 g/m<sup>2</sup>) Aratex fabric



Open-backed

Sizes: M, L

EN 340/EN ISO 11612

Category III PPE

### MARKING

Ref.	Product	MARKING		
901.288	OVERALL Size M Chest width: 620 mm / Sleeve length: 650 mm / Length: 1.110 mm		A1	A2
901.289	OVERALL Size L Chest width: 710 mm / Sleeve length: 670 mm / Length: 1.130 mm		B1	B2 B3
			C1	C2 C3 C4
			D1	D2 D3
			E1	E2 E3
			F1	F2 F3

## Body protection: aluminised clothing

<b>Standard and certification</b>	EN 340 / EN ISO 11612 Category III PPE
<b>Applications</b>	PPE for industrial use in the following sectors: foundries, metal industry, pyrotechnics, furnace repair, cement works, steelworks, etc.
<b>Conservation Storage - Expiry</b>	Protect from light and dust. Not washable. Clean with a damp sponge. Do not dry clean.
<b>Directions Use</b>	Adjustable at the back using Velcro and then using the waist strap, connecting both buckles and adjusting to the correct fit. Correct performance of the garment requires it to be correctly adjusted. This equipment is designed for use during short periods.
<b>Presentation</b>	Individually packed: 1 unit.
<b>Bar code</b>	OVERALL Ref. 901.288 GTIN-13: 8423173100315    GTIN-14: 18423173100312  OVERALL Ref. 901.289 GTIN-13: 8423173100322    GTIN-14: 18423173100329

