

P1 Spherical with valve





Respiratory protection: Filter Masks

Description and Composition:

Spherical shape self filtering mask that facilitates optimal adaptation to the face. Soft surface both inside and outside: cotton feeling.

Double sided material for maximum resistance to heat and moisture. Special anti filtering sealing around the edge of the self filtering mask. Adjustable nose clip with foam inside.

Latex free double adjustment rubber strap. Incorporates exhalation valve to provide additional comfort in hot environments and avoid heat and humidity build up inside the mask.

Maximum level of use: <4xTLV

FFP1 NR

Ref.	Product
911.160	P1 Spherical with valve

Characteristics		
Active Carbon	X	
Dolomite Test	X	
With Valve	\checkmark	
Latex free	\checkmark	
Metal free	X	
Individual bags	X	
Size	Unic	
Weight	15 gr.	



Internal cushion.



Exhalation valve.



Adaptable clip.

Respiratory protection: Filter Masks

Standard and Certificacion	EN 149:2001 + A1:2009 CE 0086
Aplications	Offers protection against solid and liquid particles with a low level of toxicity in low concentrations. Never use to filter gases or vapours. Do not use in environments containing less than 17% oxygen by volume, nor in explosive atmospheres. Inert dusts and aerosols that do not affect the respiratory tracts. Limit value >10 mg/m3 (4 x TLV). USES: sanding, deburring, grinding, drilling. Construction. Biological/Allergens: pollen. Agriculture, livestock sector.
Maintenance Storage - Expiry date	Store the equipment in its package, in a cool, well-ventilated place, avoiding moisture, filth and dust.
Instructions Use - How to Employ	Dispose of the mask after use. Designed for one-time use only. Dispose of the mask if it offers great resistance to breathing.
Presentation Pr	Box of 10 units. Carton of 12 boxes.
Barcode	GTIN-13: 8423173871222 GTIN-14: 28423173871226

