

P2 Spherical with valve



Respiratory protection: Filter Masks

Description and Composition:


Its spherical shape facilitates optimum adaptation to the face. Incorporates an adjustable nose clip with foam inside. Double rubber adjustment band.

Incorporates exhalation valve to provide additional comfort in hot environments and avoid heat and humidity build up inside the mask.

Materials: Polyester and polypropylene.

Maximum level of use: <12xTLV

FFP2 NR



Characteristics	
Active Carbon	X
Dolomite Test	X
With Valve	\checkmark
Latex free	\checkmark
Metal free	X
Individual bags	X
Size	Unic
Weight	12 gr.



Internal cushion.



Exhalation valve.



Double adjustment strap for a uniform fit.

Respiratory protection: Filter Masks

Barcode

Standard and Certificacion	EN 149:2001+A1:2009 CE 0086
Aplications	Offers protection against solid and liquid particles of low and medium toxicity (against solid and liquid aerosols). Never use to filter gases or vapours. Do not use in environments containing less than 17% oxygen by volume, nor in explosive atmospheres. Inert dusts and aerosols that can affect the respiratory tracts. USES: sanding, deburring, grinding, drilling. Construction. Metal working foundries. Biological/Allergens: fungi, viruses. Agriculture, livestock sector. Mining/Quarrying. Ceramics.
Maintenance Storage - Expiry date	Store the equipment in its package, in a cool, well-ventilated place, avoiding moisture, filth and dust.
Instructions Use - How to Employ	Dispose of the mask after use. Designed for one-time use only. Dispose of the mask if it offers great resistance to breathing.
Presentation Second	Box of 10 units. Carton of 20 boxes.



GTIN-13: 8423173116309 GTIN-14: 38423173116300