

P2 RD PAD filter



Respiratory protection: filters

Description and composition:

This filter is made using cutting-edge filtration materials: Advanced Non-wovens Fiber

Maximum breathability: air chamber design to guarantee lower breathabilities.

It is designed to offer excellent protection against:

Solid and liquid particles, such as dust, smoke, aerosols...

This filter may be used with all Medop half masks with a bayonet connection.

Maximum level of use:

Particle filter - Use level 2: Limit value 5000 ppm; 0.5% volum. Between 10 mg/m³ and 0.1 mg/m³ (12 x TLV)

Reusable

Passes the dolomite test.

Weight: 13.1 g

Ref.	Product
912.086	P2 bayonet filter



Bayonet connection



Protection against: Particles.



Extremely lightweight. Over 70% weight reduction compared to a standard filter.

Respiratory protection: filters

Standard and certification	EN 143 CE/EN 14387 CE
Applications	Degreasing, work with concrete, bricks, stone and plaster, fi bre glass and mineral fibre processing, sand blasting, wood shredding, rust, metals and steel, welding, paint, contact with mould, pesticide spraying. Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way: XX/XXXX (MONTH/YEAR)
Directions Use	This filterf ilters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19.5% volume. Immediately leave the work area and replace your filters if during use: - You find it hard to breathe - You feel dizzy or vertigo - You smell or taste contaminant
Presentation	2 units per bag 10 pairs per box 12 boxes per carton Measurements: 140 x 84 mm
Bar code	GTIN-13: 8423173879709 GTIN-14: 18.423.173.879.706

