



P3 Conical with valve



Respiratory protection: Filter Masks

Description and Composition:


Internal side made of polypropylene, giving the mask a soft cover. Includes foam nose cushion and adjustable latex free band for a better grip.

Incorporates exhalation valve to provide additional comfort in hot environments and avoid heat and humidity build up inside the mask.

Dolomite Test Passed: less obstruction during use.

Maximum level of use: <50xTLV


FFP3 NR D



Internal cushion.



Exhalation valve.




Double adjustment strap for a uniform fit.

Ref.	Product
910.339	P3 Conical with valve

Characteristics	
Active Carbon	X
Dolomite Test	✓
With Valve	✓
Latex free	✓
Metal free	✓
Individual bags	X
Size	Unic
Weight	23 gr.

Respiratory protection: Filter Masks

Standard and Certification	EN 149 CE
Applications	<p>Offers protection against solid and liquid particles of medium and high toxicity (against solid and liquid aerosols, metallic smoke and smoke from welding or smelting processes). Never use to filter gases or vapours.</p> <p>Do not use in environments containing less than 17% oxygen by volume, nor in explosive atmospheres. High concentrations of dust and particles that can affect the respiratory tracts. Limit value <math><0.1 \text{ mg/m}^3</math> (50 x TLV).</p> <p>USES: sanding, deburring, grinding, drilling.</p> <p>Construction. Metal working foundries. Biological/Allergens: fungi, viruses. Agriculture, livestock sector. Mining/Quarrying. Ceramics. Wood Industry.</p>
Maintenance Storage - Expiry date	Store the equipment in its package, in a cool, well-ventilated place, avoiding moisture, filth and dust.
Instructions Use - How to Employ	Dispose of the mask after use. Designed for one-time use only. Dispose of the mask if it offers great resistance to breathing.
Presentation	<p>Box of 10 units. Carton of 12 boxes.</p> 
Barcode	GTIN-13: 8423173839871 GTIN-14: 28423173839875

