



P3 RD PAD Filter



Respiratory protection: filters

Description and composition:

This filter is made using cutting-edge filtration materials:
Advanced Non-wovens Fiber

Maximum breathability: air chamber designed to guarantee lower breathabilities.

It is designed to offer excellent protection against:
solid and liquid particles, such as dust, smoke, aerosols...


This filter may be used with all Medop half masks with a bayonet connection.

Maximum level of use:
Particle filter - Use level 3: Limit value 10000 ppm; 1% volum. 0.1 mg/m³ (50 x TLV)

Reusable

Passes the dolomite test.

Weight: 13.9 g



Bayonet connection



Protection against:
Particles.



Extremely lightweight. Over 70% weight reduction compared to a standard filter.

Ref.	Product
912.087	P3 bayonet filter

Respiratory protection: filters

Standard and certification	EN 143 CE/EN 14387 CE
Applications	Asbestos removal, work with chrome-containing paint, work with beech and oak wood, stainless steel, cutting with laser light, certain types of welding, dust sweeping, electrical stations... Do not use in atmospheres with less than 19,5% oxygen content volume.
Conservation Storage - Expiry	Store in storage case in a cool, well ventilated place, avoiding humidity, dirt and dust. Shelf life of the filters is indicated on them and is valid for sealed wrappers. The expiry date is marked in the following way: XX/XXXX (MONTH/YEAR) 🕒
Directions Use	This filter filters contaminated air, but it does not provide oxygen. Thus, it must not be used when the ambient oxygen content is below 19,5% volume. Immediately leave the work area and replace your filters if during use: - You find it hard to breathe - You feel dizzy or vertigo - You smell or taste contaminant
Presentation	2 units per bag 10 pairs per box 12 boxes per carton Measurements: 140 x 84 mm
Bar code	GTIN-13: 8423173879891 GTIN-14: 18423173879898

