



Foldable



Hearing protection: headphones

Description and composition:

Buffers made in hypo-allergenic materials.

- Headband: POM
- Ear cups: plastic
- Bridge between headband and ear cups: metal


Extendible headband, allowing use with helmets. **Folding**, making these headphones especially light and easy to transport and store.

Net weight: 218 g

SNR 31



Adjustable height



Cushioned ear pads



Metallic arch

Ref.	Product
903.000	Foldable

Characteristics table	
Cushioned headband	✓
Adjustable height	✓
Cushioned ear pads	✓
Electronic	✗
0% metal	✗

Hearing protection: headphones

Standard and certification	EN 352-1 CE																																										
Applications	The product offers high attenuation, whereby it is especially recommended for high-noise environments and activities where worker visibility is important. Work environments with a noise level between: 100 dB and 115 dB. Sectors: F&B, chemical, metallurgy, carpentry, automotive industry, construction, graphic arts, airports, etc.																																										
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																										
Directions Use	Clean regularly with soap and water. Inspect regularly and replace immediately when damaged or very worn. This equipment is for personal use and should not be used by several people. The headphones must be worn continually in noisy areas.																																										
Presentation	10 units per box. 6 units per carton.																																										
Bar code	GTIN-13: 8423173117412 GTIN-14: 28423173117416																																										
Technical data:	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>93</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>8000</th> </tr> </thead> <tbody> <tr> <td>Average attenuation</td> <td>18.6</td> <td>16.0</td> <td>21.3</td> <td>31.4</td> <td>38.8</td> <td>35.9</td> <td>37.0</td> <td>37.0</td> </tr> <tr> <td>Typical deviation</td> <td>3.9</td> <td>2.5</td> <td>2.4</td> <td>2.5</td> <td>3.9</td> <td>3.0</td> <td>2.3</td> <td>2.1</td> </tr> <tr> <td>Assumed attenuation</td> <td>14.7</td> <td>13.4</td> <td>18.8</td> <td>28.9</td> <td>34.9</td> <td>32.9</td> <td>34.7</td> <td>34.8</td> </tr> </tbody> </table> <table border="1"> <tr> <td>Global attenuation in frequencies</td> <td>High (H) H = 34.4</td> <td>Mid (M) M = 29.1</td> <td>Low (L) L = 20.6</td> <td>SNR</td> <td>31</td> </tr> </table>	Frequency in Hz	93	125	250	500	1000	2000	4000	8000	Average attenuation	18.6	16.0	21.3	31.4	38.8	35.9	37.0	37.0	Typical deviation	3.9	2.5	2.4	2.5	3.9	3.0	2.3	2.1	Assumed attenuation	14.7	13.4	18.8	28.9	34.9	32.9	34.7	34.8	Global attenuation in frequencies	High (H) H = 34.4	Mid (M) M = 29.1	Low (L) L = 20.6	SNR	31
Frequency in Hz	93	125	250	500	1000	2000	4000	8000																																			
Average attenuation	18.6	16.0	21.3	31.4	38.8	35.9	37.0	37.0																																			
Typical deviation	3.9	2.5	2.4	2.5	3.9	3.0	2.3	2.1																																			
Assumed attenuation	14.7	13.4	18.8	28.9	34.9	32.9	34.7	34.8																																			
Global attenuation in frequencies	High (H) H = 34.4	Mid (M) M = 29.1	Low (L) L = 20.6	SNR	31																																						

