



Que se Callen



Hearing protection: headphones

Description and composition:

Buffers made in hypo-allergenic materials.

This model incorporates cushioned headband as well as height adjustable ear cups for greater comfort and adaptability.

The eye-catching colours make these headphones ideal for activities where worker visibility is important.

Dielectric: with no metal parts.

Net weight: 294 g



Adjustable height



Cushioned ear pads



0%
metal

0% metal

Ref.	Product
906.993	Que se Callen

Characteristics table	
Cushioned headband	✓
Adjustable height	✓
Cushioned ear pads	✓
Electronic	✗
0% metal	✓

Hearing protection: headphones

Standard and certification	EN 352-1 CE																																		
Applications	The product offers high attenuation, whereby it is especially recommended for high-noise environments and activities where worker visibility is important. Work environments with a noise level between: 103 dB and 118 dB. Sectors: F&B, chemical, metallurgy, carpentry, automotive industry, construction, graphic arts, airports, etc.																																		
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																		
Directions Use	Clean regularly with soap and water. Inspect regularly and replace immediately when damaged or very worn. This equipment is for personal use and should not be used by several people. The headphones must be worn continually in noisy areas.																																		
Presentation	10 units per box. 20 boxes per carton.																																		
Bar code	GTIN-13: 8423173134693 GTIN-14: 88423173134699																																		
Technical data:	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1,000</th> <th>2,000</th> <th>4,000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Assumed attenuation</td> <td>19.6</td> <td>20.9</td> <td>28.2</td> <td>38.3</td> <td>33.8</td> <td>35.7</td> <td>31.5</td> </tr> <tr> <td>Typical deviation</td> <td>3.2</td> <td>3.5</td> <td>3.4</td> <td>3.4</td> <td>3.5</td> <td>3.7</td> <td>4.4</td> </tr> <tr> <td>Average attenuation</td> <td>22.8</td> <td>24.4</td> <td>31.6</td> <td>41.7</td> <td>37.3</td> <td>39.4</td> <td>35.9</td> </tr> </tbody> </table> <table border="1"> <tr> <td>SNR</td> <td>33</td> </tr> </table>	Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000	Assumed attenuation	19.6	20.9	28.2	38.3	33.8	35.7	31.5	Typical deviation	3.2	3.5	3.4	3.4	3.5	3.7	4.4	Average attenuation	22.8	24.4	31.6	41.7	37.3	39.4	35.9	SNR	33
Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000																												
Assumed attenuation	19.6	20.9	28.2	38.3	33.8	35.7	31.5																												
Typical deviation	3.2	3.5	3.4	3.4	3.5	3.7	4.4																												
Average attenuation	22.8	24.4	31.6	41.7	37.3	39.4	35.9																												
SNR	33																																		

