



# RULER

DESIGN AND COMFORT

RX  
Prescription  
**NEUTRAL**  
Non-prescription

UV  
400

WEIGHT  
37 g



Certified under the following regulations:  
EN ISO 18526  
UNE-EN ISO 8980-1:2018  
UNE-EN ISO 8980-2:2018  
EN166 and EN170



ANTI-FATIGUE AND PROTECTION AGAINST HARMFUL LIGHT

Antifog

ANTI-FOGGING Safe to use in conjunction with respiratory protection and in workplaces where there is a risk of fogging. Treatment applied to all non-prescription lenses.



IMPACT PROTECTION AND ANTI-SCRATCH COATING: Safety for strong and long-lasting spectacles



## SAFETY SPECTACLES with a very modern design FOR THE OFFICE OR INDUSTRY.

The RULER model combines HEALTH and SAFETY thanks to the technical requirements of the frame and its lenses, both in the NEUTRAL (non-prescription) and PRESCRIPTION versions. This model is designed for taking care of workplace safety and eye health.

- Nylon frame: **LIGHTWEIGHT** material with **HIGH** impact **RESISTANCE**
- Anti-slip temple-ends: excellent **ADHERENCE** for a more comfortable, safer time at work
- Temples with a metal core: **ALLOWS** for easily **ADAPTING** the temples, without the need for tools
- **Wide, REMOVABLE** side protectors
- **2 sizes, 3 colours**

MATERIALS	
Frame and nasal bridge	NYLON
Temples	NYLON and metal (copper-brass alloy) 133 mm
Screw	Stainless steel
Lenses	Base 5
Calibres	Size M: 50-21 mm Size L: 51-21 mm

OTHER COMPONENTS	
Silicone*	Not present
Latex*	Not present
Metal	Present

\* Although this PPE does not contain latex or silicone, it is recommended to perform tests and try out the product in the areas where it is going to be used.

## MARKING INFORMATION

Standards and certifications	EN ISO 18526-2 Point 9.2.: Blue-light transmittance from artificial sources (380 - 500 nm)
	EN 166: Personal eye protection. Occupational safety
	EN 170: Ultraviolet filter. Occupational safety. Grade 2C-1.2: maximum spectral transmittance for $T(\lambda)$ ultraviolet light at 313 nm (0.0003%) and at 365 nm (10%).
	EU 2016/425 Regulation (class 2 PPE)
	UNE-EN ISO 8980-1, Specifications for single-vision and multifocal lenses
	UNE-EN ISO 8980-2, Specifications for progressive lenses.
	UV 400

## PRESENTATION

NEUTRAL spectacles (non-prescription):  
1 unit polybag  
Box of 10 units  
Carton of 120 units



PRESCRIPTION spectacles:  
Case, spectacles retainer and cleaning cloth. The prescription spectacles include a customer card indicating their prescription.



# CORRECTIVE lenses in different MATERIALS, TREATMENTS, and PRESCRIPTIONS

## FULL ADAPTABILITY TO ALL WORKING CONDITIONS

- **ULTRAVIOLET PROTECTION:** Certified under the EN 170 standard (Grade 2C-1.2) for UV transmittance at 313 nm and 365 nm. Prevents UV radiation from penetrating the lens, thereby protecting against cumulative damage due to screen use. **UV 400.**
- **CERTIFIED ANTI-SCRATCH COATING** (EN166 Standard): more resistant and long-lasting lenses (All K-marking materials).
- **ANTI-REFLECTIVE COATING** providing a greater level of **LONGER-LASTING EYE COMFORT.**
- **PROTECTION AGAINST IMPACTS** of low energy and high speed at extreme temperatures in polycarbonate (FT marking) and with an increased organic and mineral resistance (S marking).
- The design of the RULER spectacles **PROMOTES THE PROPER ASSEMBLY OF PROGRESSIVE LENSES:** suitable model for all types of corrective lenses, including higher prescriptions.

PLUS EXTRA TREATMENT IF REQUIRED:

- **PROTECTIVE FILTER AGAINST HARMFUL LIGHT:** Tested according to EN ISO 18526 (Point 9.2) on the transmittance of blue light emitted by screens, mobile phones, and similar devices. It helps prevent blurred vision and headaches, and eye ageing in the long term.
- **CERTIFIED ANTI-FOGGING COATING (EN166):** They guarantee superior performance and excellent efficiency when masks and spectacles are worn together, and in environments with sudden changes in temperature.

AVAILABLE FOR <i>Prescription spectacles*</i>	Frame marking	Lens marking
Prescription spectacles with polycarbonate lenses with CERTIFIED anti-scratch coating and BPSHield (for blue light)	M EN 166 FT C €	2C-1,2 M 1 FTK C €
Prescription spectacles with polycarbonate lenses with CERTIFIED anti-scratch coating and anti-fogging coating		
Prescription spectacles with polycarbonate lenses with CERTIFIED anti-scratch coating and self-cleaning coating		
Prescription spectacles with CLEAR organic MR7 lenses with CERTIFIED anti-scratch coating and BPSHield (for blue light)		2C-1,2 M 1 SK C €
Prescription spectacles with CLEAR organic MR7 lenses with CERTIFIED anti-scratch coating and anti-fogging coating		
Prescription spectacles with CLEAR organic MR7 lenses with CERTIFIED anti-scratch coating and self-cleaning coating		
Prescription spectacles with CLEAR organic CR-39 lenses with CERTIFIED anti-scratch coating and BPSHield (for blue light)		M 1 SK C €
Prescription spectacles with CLEAR organic CR-39 lenses with CERTIFIED anti-scratch coating and anti-fogging coating		
Prescription spectacles with CLEAR organic CR-39 lenses with CERTIFIED anti-scratch coating and self-cleaning coating		
Prescription spectacles with CLEAR organic mineral lenses with CERTIFIED anti-scratch coating	M 1 SK C €	
Prescription spectacles with SOLAR organic (CR-39) lenses with CERTIFIED anti-scratch coating	5-3,1 M 1SK C €	

Prescription limits	Monofocal	Bi-focal	Progressives
POLYCARBONATE	-8.00 / +8.00	-8.00 / +8.00, Add 3.00	-6.00 / +6.00, Add 3.00
ORGANIC (CR-39)	-8.00 / +7.00	-8.00 / +0.00, Add 3.00	-8.00 / +5.00, Add 3.00
ORGANIC (MR7)	-10.00 / +10.00	-	-10.00 / +7.00, Add 3.00
MINERAL	-8.00 / +8.00	-6.00 / +6.00, Add 3.00	-6.00 / +5.00, Add 3.00

\*Consult other treatments available for prescription lenses

## HEALTH AND SAFETY: All that careyeindustry NEUTRAL LENSES have to offer

- **PROTECTIVE FILTER AGAINST HARMFUL LIGHT:** Tested according to EN ISO 18526 (Point 9.2) on the transmittance of blue light emitted by screens, mobile phones, and similar devices. It helps prevent blurred vision and headaches, and eye ageing in the long term.
- **LENS FILTER WITH LIGHTCLEAR TINT** which reduces blue light transmittance while maintaining the highest optical quality.
- **ULTRAVIOLET PROTECTION:** Certified under the EN 170 standard (Grade 2C-1.2) for UV transmittance at 313 nm and 365 nm. Prevents UV radiation from penetrating the lens, thereby protecting the eye's structures against cumulative damage due to screen use.
- **CERTIFIED ANTI-FOGGING COATING (EN166):** They guarantee superior performance and excellent efficiency when masks and spectacles are worn together, and in environments with sudden changes in temperature (**N marking**).
- **ANTI-SCRATCH COATING CERTIFIED** under the EN166 occupational safety standard: more resistant and long-lasting lenses (**K marking**).
- **PROTECTION AGAINST IMPACTS** of low energy and high speed at extreme temperatures in polycarbonate (**FT marking**).

AVAILABLE <i>Non-prescription spectacles</i>	Frame marking	Lens marking	Size	Ref.		
				Blue	Black	Grey
Non-prescription spectacles with polycarbonate  careyeindustry lenses with CERTIFIED anti-scratch and anti-fogging coatings	M EN 166 FT C €	2C-1,2 M 1 FTKN C €	M	914458	914459	914460
			L	914476	914477	914478

## OTHER FEATURES

Uses	Jobs with a risk of IMPACTS ● Risk of FOGGING (due to rapid changes in temperature or for using in conjunction with respiratory protection) ● Jobs with exposure to ULTRAVIOLET LIGHT ● Jobs with exposure to BLUE LIGHT  Typical jobs: industry in general, but especially recommended for parts inspectors, call centres, workshops, graphic arts, etc... and generally recommended for office jobs and those with data display screens (computers, mobile devices, tablets, process control screens, etc.).																		
Conservation Storage Expiry	For better conservation of the spectacles, they must be stored in a cool and ventilated place, away from moisture, dirt and dust. It is recommended that you use a suitable case for storage and transport.																		
Instructions Use How to use	Spectacles <b>should be regularly cleaned</b> with clean, warm water and soap, no abrasives or solvents. Rinse in water and dry with a clean, soft and absorbent cloth. <b>For a more thorough cleaning</b> (disinfection), please use a dry cloth dipped in alcohol. Never use any other type of solvent. It is necessary to <b>regularly inspect the state of the spectacles</b> , and replace them if they have deteriorated in any way.																		
Presentation	Neutral version: 1 unit polybag / Box of 10 units  Prescription version: Case, spectacles retainer and cleaning cloth. The prescription spectacles include a customer card indicating their prescription.																		
Bar code	<table border="0"> <tr> <td>914458</td> <td><b>GIN-13:</b> 8423173895068</td> <td><b>GIN14:</b> 18423173895065</td> </tr> <tr> <td>914459</td> <td><b>GIN-13:</b> 8423173895075</td> <td><b>GIN14:</b> 18423173895072</td> </tr> <tr> <td>914460</td> <td><b>GIN-13:</b> 8423173895082</td> <td><b>GIN14:</b> 18423173895089</td> </tr> <tr> <td>914476</td> <td><b>GIN-13:</b> 8423173895242</td> <td><b>GIN14:</b> 18423173895249</td> </tr> <tr> <td>914477</td> <td><b>GIN-13:</b> 8423173895259</td> <td><b>GIN14:</b> 18423173895256</td> </tr> <tr> <td>914478</td> <td><b>GIN-13:</b> 8423173895266</td> <td><b>GIN14:</b> 18423173895263</td> </tr> </table>	914458	<b>GIN-13:</b> 8423173895068	<b>GIN14:</b> 18423173895065	914459	<b>GIN-13:</b> 8423173895075	<b>GIN14:</b> 18423173895072	914460	<b>GIN-13:</b> 8423173895082	<b>GIN14:</b> 18423173895089	914476	<b>GIN-13:</b> 8423173895242	<b>GIN14:</b> 18423173895249	914477	<b>GIN-13:</b> 8423173895259	<b>GIN14:</b> 18423173895256	914478	<b>GIN-13:</b> 8423173895266	<b>GIN14:</b> 18423173895263
914458	<b>GIN-13:</b> 8423173895068	<b>GIN14:</b> 18423173895065																	
914459	<b>GIN-13:</b> 8423173895075	<b>GIN14:</b> 18423173895072																	
914460	<b>GIN-13:</b> 8423173895082	<b>GIN14:</b> 18423173895089																	
914476	<b>GIN-13:</b> 8423173895242	<b>GIN14:</b> 18423173895249																	
914477	<b>GIN-13:</b> 8423173895259	<b>GIN14:</b> 18423173895256																	
914478	<b>GIN-13:</b> 8423173895266	<b>GIN14:</b> 18423173895263																	

