



Rumor IV



Hearing protection: headphones

Description and composition:

Very light buffers made in hypo-allergenic materials.

Materials:

- Headband: POM
- Cups: ABS (acrylonitrile butadiene styrene)
- Cup padding: polyurethane

Adjusts to a wide range of sizes. Extremely comfortable thanks to their light weight. Personalized adjustment.

Net weight: 152 g

SNR 26


Ref.	Product
902.872	Rumor IV

Characteristics table

Cushioned headband	✓
Adjustable height	✓
Cushioned ear pads	✓
Electronic	✗
0% metal	✓



Adjustable height



Cushioned ear pads



0%
metal

0% metal

Hearing protection: headphones

Standard and certification	EN 352-1 CE																																																					
Applications	The product offers high attenuation, whereby it is especially recommended for high-noise environments and activities where worker visibility is important. Work environments with a noise level between: 95 dB and 110 dB. Sectors: F&B, chemical, metallurgy, carpentry, automotive industry, construction graphic arts, forestry, etc.																																																					
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																																					
Directions Use	Clean regularly with soap and water. Inspect regularly and replace immediately when damaged or very worn. This equipment is for personal use and should not be used by several people. The headphones must be worn continually in noisy areas.																																																					
Presentation	10 units per box. 6 boxes per carton.																																																					
Bar code	GTIN-13: 8423173116132 GTIN-14: 28423173116136																																																					
Technical data:	<table><tr><td>Frequency in Hz</td><td>63</td><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td><td>8000</td></tr><tr><td>Assumed attenuation</td><td>8,8</td><td>7,8</td><td>12,7</td><td>22,8</td><td>32</td><td>29</td><td>39,4</td><td>33,1</td></tr><tr><td>Typical deviation</td><td>4,6</td><td>3</td><td>2,8</td><td>2,6</td><td>2,6</td><td>3,1</td><td>2,2</td><td>4,1</td></tr><tr><td>Average attenuation</td><td>13,4</td><td>10,8</td><td>15,5</td><td>25,4</td><td>34,6</td><td>32,1</td><td>41,6</td><td>37,2</td></tr><tr><td>Global attenuation in frequencies</td><td colspan="2">High (H) H = 32</td><td colspan="2">Mid (M) M = 23</td><td colspan="2">Low (L) L = 14</td><td>SNR</td><td>26</td></tr></table>									Frequency in Hz	63	125	250	500	1000	2000	4000	8000	Assumed attenuation	8,8	7,8	12,7	22,8	32	29	39,4	33,1	Typical deviation	4,6	3	2,8	2,6	2,6	3,1	2,2	4,1	Average attenuation	13,4	10,8	15,5	25,4	34,6	32,1	41,6	37,2	Global attenuation in frequencies	High (H) H = 32		Mid (M) M = 23		Low (L) L = 14		SNR	26
Frequency in Hz	63	125	250	500	1000	2000	4000	8000																																														
Assumed attenuation	8,8	7,8	12,7	22,8	32	29	39,4	33,1																																														
Typical deviation	4,6	3	2,8	2,6	2,6	3,1	2,2	4,1																																														
Average attenuation	13,4	10,8	15,5	25,4	34,6	32,1	41,6	37,2																																														
Global attenuation in frequencies	High (H) H = 32		Mid (M) M = 23		Low (L) L = 14		SNR	26																																														

