



Run-Run



Hearing protection: earplugs

Description:


Pre-moulded earplug in hypo-allergenic silicone prevents skin conditions. Loss-prevention security cord.

Hygienic insertion: no need to adapt them or handle the part in contact with the ear.

SNR: 21 dB

Weight: 2.67 g


EN 352-2 CE



Silicone



Loss-prevention cord



| Ref. | Product |
|---------|---------|
| 900.825 | Run-Run |

| Characteristics table | |
|-----------------------|---|
| Washable | ✓ |
| Hypo-allergenic | ✓ |
| Reusable | ✓ |
| Single use | ✗ |
| Detectable | ✗ |
| Cord | ✓ |

Hearing protection: earplugs

| | |
|--|--|
| Standard and certification | EN 352-2 CE |
| Applications | Workplaces with high temperatures. Intermittent exposure to noise. Work environments with a high noise level between 92 dB and 107 dB. General industrial use. |
| Conservation Storage - Expiry | Store in a cool, dry place in their case, avoiding humidity, dirt and dust. They are reusable and washable in soap and water. |
| Directions Use | They are reusable and washable in warm soapy water; rinse and dry. This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas. These plugs must not be used in environments where there is a risk of the joining cord being snagged during use. |
| Presentation | 1 pair per case. Bag with 25pairs in individual bags. 64 bagas per carton. |



| | |
|-----------------|--|
| Bar code | GTIN-13: 8423173095703 GTIN-14: 44842317309575 |
|-----------------|--|

| Attenuation table | <table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>65</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>8000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Assumed attenuation</td> <td>17,7</td> <td>19,9</td> <td>17,9</td> <td>17,4</td> <td>17,8</td> <td>27,6</td> <td>27,6</td> <td>15,3</td> <td>25.4</td> </tr> <tr> <td>Typical deviation</td> <td>4,8</td> <td>3,5</td> <td>3,7</td> <td>3,6</td> <td>4,1</td> <td>3,5</td> <td>4,0</td> <td>6,2</td> <td>6.2</td> </tr> <tr> <td>Average attenuation</td> <td>22,5</td> <td>23,4</td> <td>21,6</td> <td>21,0</td> <td>21,9</td> <td>31,1</td> <td>31,6</td> <td>21,5</td> <td>19.2</td> </tr> <tr> <td>Global attenuation in frequencies</td> <td colspan="3">High (H) H = 21</td> <td colspan="3">Mid (M) M = 19</td> <td colspan="2">Low (L) L = 19</td> <td>SNR</td> <td>21</td> </tr> </tbody> </table> | | | | | | | | | | Frequency in Hz | 65 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | 8,000 | Assumed attenuation | 17,7 | 19,9 | 17,9 | 17,4 | 17,8 | 27,6 | 27,6 | 15,3 | 25.4 | Typical deviation | 4,8 | 3,5 | 3,7 | 3,6 | 4,1 | 3,5 | 4,0 | 6,2 | 6.2 | Average attenuation | 22,5 | 23,4 | 21,6 | 21,0 | 21,9 | 31,1 | 31,6 | 21,5 | 19.2 | Global attenuation in frequencies | High (H) H = 21 | | | Mid (M) M = 19 | | | Low (L) L = 19 | | SNR | 21 |
|-----------------------------------|--|------|------|-------------------|------|------|-------------------|------|-------|----|-----------------|----|-----|-----|-----|------|------|------|------|-------|---------------------|------|------|------|------|------|------|------|------|------|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|---------------------|------|------|------|------|------|------|------|------|------|-----------------------------------|--------------------|--|--|-------------------|--|--|-------------------|--|-----|----|
| Frequency in Hz | 65 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | 8,000 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Assumed attenuation | 17,7 | 19,9 | 17,9 | 17,4 | 17,8 | 27,6 | 27,6 | 15,3 | 25.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Typical deviation | 4,8 | 3,5 | 3,7 | 3,6 | 4,1 | 3,5 | 4,0 | 6,2 | 6.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Average attenuation | 22,5 | 23,4 | 21,6 | 21,0 | 21,9 | 31,1 | 31,6 | 21,5 | 19.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Global attenuation in frequencies | High (H) H = 21 | | | Mid (M) M = 19 | | | Low (L) L = 19 | | SNR | 21 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

