

Detectable Sigilo Plus

Hearing protection: earplugs

Description:

Hypo-allergenic silicone earplug for continuous and comfortable protection

Pre-moulded: no need to adapt them before inserting. Their triple-cone design eases insertion, providing perfect protection and great comfort, even with prolonged use.

Hygienic insertion: no need to touch the plug when inserting. With safety PVC cord to avoid loss of plugs. **Containing metal detectors: specially designed for the food industry.**

SNR: 30 dB

Weight: 3.43 g

EN 352-2 CE

Ref.	Product	Characteristics table					
911649	Detectable Sigilo Plus	Washable	\checkmark				
		Hypo-allergenic	\checkmark				
		Reusable	\checkmark				
		Single use	X	•			
		Detectable	\checkmark				
		. Cord	\checkmark				
		Nominal size	7-11	Ň			

Detectable



SNR

Loss-prevention PVC cord



www.medop.es

Hearing protection: earplugs

Standard and certification	EN 352-2 CE												
Applications	Workplaces with high temperatures. Intermittent exposure to noise. Work environments with a high noise level between 100 dB and 115 dB. General industrial use, however especially recommended for food and beverage industry.												
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust. They are reusable and washable in soap and water.												
Directions Use	They are reusable and washable in warm soapy water, rinse and dry. This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas. These plugs must not be used in environments where there is a risk of the joining cord being snagged during use.												
Presentation	Pairs in individual bags. Bag with 25 pairs. 20 boxes per bags.												
Bar code	GTIN-13: 8423173875657 GTIN-14: 88842317387560												
Attenuation table	Frequency in Hz Average attenuation Typical deviation Assumed attenuation Global attenuation in frequencies	63 31.6 5.6 26.0 High H =	125 32.7 5.7 27.0 • (H) 27	250 30.9 5.9 25.0 Mid (M = 2		1,000 37.4 8.1 29.3 Low (L) L = 27	2,000 29.9 5.1 24.8	4,000 40.3 7.7 32.6	8,000 44.6 5.0 39.6 30				

