



Tímpano



Hearing protection: earplugs

Description:

Manufactured in hypo-allergenic TPR (thermoplastic rubber). A malleable material that is very resistant to ageing and abrasion.

Pre moulded: no need to adapt them before inserting. Their triple-cone design eases insertion, providing perfect protection and great comfort, even with prolonged use.

Hygienic insertion: no need to touch the plug when inserting. Loss-prevention security cord.

SNR: 27 dB

Weight: 2.64 g


EN 352-2 CE



Triple seal



Loss-prevention cord



Ref.	Product
910350	Tímpano

Characteristics table	
Washable	✓
Hypo-allergenic	✓
Reusable	✓
Single use	✗
Detectable	✗
Cord	✓
Nominal size	7-12

Hearing protection: earplugs

Standard and certification	EN 352-2 CE																																						
Applications	Workplaces with high temperatures. Intermittent exposure to noise. Work environments with a high noise level between 96 dB and 111 dB. General industrial use.																																						
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust. They are reusable and washable in soap and water.																																						
Directions Use	They are reusable and washable in warm soapy water; rinse and dry. This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas. These plugs must not be used in environments where there is a risk of the joining cord being snagged during use.																																						
Presentation	1 pair per case. Bag of 25 pairs. 40 bags per carton. <div data-bbox="815 663 1161 920" data-label="Image"> </div>																																						
Bar code	GTIN-13: 8423173840013 GTIN-14: 28423173840017																																						
Attenuation table	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1,000</th> <th>2,000</th> <th>4,000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Average attenuation</td> <td>25.3</td> <td>24.6</td> <td>26.8</td> <td>26.4</td> <td>30.1</td> <td>36.1</td> <td>40.4</td> </tr> <tr> <td>Typical deviation</td> <td>4.5</td> <td>4.9</td> <td>3.4</td> <td>3.3</td> <td>4.3</td> <td>3.5</td> <td>6.1</td> </tr> <tr> <td>Minimum attenuation</td> <td>20.8</td> <td>19.7</td> <td>23.4</td> <td>23.1</td> <td>25.8</td> <td>32.6</td> <td>34.3</td> </tr> </tbody> </table> <table border="1"> <tbody> <tr> <td>Global attenuation in frequencies</td> <td>High (H) H = 27</td> <td>Mid (M) M = 24</td> <td>Low (L) L = 22</td> <td>SNR</td> <td>27</td> </tr> </tbody> </table>	Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000	Average attenuation	25.3	24.6	26.8	26.4	30.1	36.1	40.4	Typical deviation	4.5	4.9	3.4	3.3	4.3	3.5	6.1	Minimum attenuation	20.8	19.7	23.4	23.1	25.8	32.6	34.3	Global attenuation in frequencies	High (H) H = 27	Mid (M) M = 24	Low (L) L = 22	SNR	27
Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000																																
Average attenuation	25.3	24.6	26.8	26.4	30.1	36.1	40.4																																
Typical deviation	4.5	4.9	3.4	3.3	4.3	3.5	6.1																																
Minimum attenuation	20.8	19.7	23.4	23.1	25.8	32.6	34.3																																
Global attenuation in frequencies	High (H) H = 27	Mid (M) M = 24	Low (L) L = 22	SNR	27																																		

