



Ultrasoft



Hearing protection: Earplugs

Description:

Manufactured in hypo-allergenic, low density foam.

Surface treated to absorb less humidity.

Hypo-allergenic.

Their conical, contoured shape makes them easy to insert.

SNR: 27 dB

Weight: 0.91 g


EN 352-2 CE



Contoured shape for maximum comfort



Triple seal



Ref.	Product
911.260	Ultrasoft

Characteristics table	
Washable	X
Hypo-allergenic	✓
Reusable	X
DSingle use	✓
Detectable	X
Cord	X
Nominal size	6-13

Hearing protection: Earplugs

Standard and certification	EN 352-2 CE																																										
Applications	Workplaces with high temperatures. Exposure to continuous noise. Work environments with a medium noise level between 98 dB and 112 dB. General industrial use.																																										
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																										
Directions Use	This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas.																																										
Presentation	Dispenser box with 200 pairs in individual bags. 10 boxes per carton.																																										
Bar code	GTIN-13: 8423173872328 GTIN-14: 88423173872324																																										
Attenuation table	<table border="1"> <thead> <tr> <th>Frequency in Hz</th> <th>63</th> <th>125</th> <th>250</th> <th>500</th> <th>1,000</th> <th>2,000</th> <th>4,000</th> <th>8,000</th> </tr> </thead> <tbody> <tr> <td>Average attenuation</td> <td>24.4</td> <td>25.5</td> <td>25.9</td> <td>26.5</td> <td>27.8</td> <td>31.9</td> <td>39.7</td> <td>41.5</td> </tr> <tr> <td>Typical deviation</td> <td>5.8</td> <td>4.1</td> <td>5.0</td> <td>6.3</td> <td>5.3</td> <td>4.9</td> <td>5.5</td> <td>5.7</td> </tr> <tr> <td>Assumed attenuation</td> <td>18.6</td> <td>21.4</td> <td>20.9</td> <td>20.2</td> <td>22.5</td> <td>27.0</td> <td>34.2</td> <td>35.8</td> </tr> </tbody> </table> <table border="1"> <tr> <td>Global attenuation in frequencies</td> <td>High (H) H = 28</td> <td>Mid (M) M = 23</td> <td>Low (L) L = 22</td> <td>SNR</td> <td>27</td> </tr> </table>	Frequency in Hz	63	125	250	500	1,000	2,000	4,000	8,000	Average attenuation	24.4	25.5	25.9	26.5	27.8	31.9	39.7	41.5	Typical deviation	5.8	4.1	5.0	6.3	5.3	4.9	5.5	5.7	Assumed attenuation	18.6	21.4	20.9	20.2	22.5	27.0	34.2	35.8	Global attenuation in frequencies	High (H) H = 28	Mid (M) M = 23	Low (L) L = 22	SNR	27
Frequency in Hz	63	125	250	500	1,000	2,000	4,000	8,000																																			
Average attenuation	24.4	25.5	25.9	26.5	27.8	31.9	39.7	41.5																																			
Typical deviation	5.8	4.1	5.0	6.3	5.3	4.9	5.5	5.7																																			
Assumed attenuation	18.6	21.4	20.9	20.2	22.5	27.0	34.2	35.8																																			
Global attenuation in frequencies	High (H) H = 28	Mid (M) M = 23	Low (L) L = 22	SNR	27																																						

